

**Annex 1 to draft Recommendation 12/1 (JCOMM-III)**

**AMENDMENTS TO THE *MANUAL ON MARINE METEOROLOGICAL SERVICES* (WMO-No. 558) AND *GUIDE TO MARINE METEOROLOGICAL SERVICES* (WMO-No. 471)**

**LAYOUT FOR THE INTERNATIONAL MARITIME METEOROLOGICAL TAPE (IMMT) FORMAT  
IMMT-IV (Version 4)**

**Notes:**

- (a) **Highlighting** marks noteworthy changes (including additional clarification Notes in [brackets]) with respect to IMMT-III.
- (b) The representation for missing data in any field is all blank(s).
- (c) Many of the "Codes" in the IMMT format match "symbolic letters" as defined in the *Manual on Codes* (WMO-No.306) for the traditional alphanumeric (FM 13-XII Ext.) SHIP code. However, the elements added for the VOSclim project (as introduced for IMMT-II), for example, did not appear in WMO-No.306, thus an effort was made to select unique new Codes to avoid conflicts in meaning between symbolic letter groups in WMO-No.306 versus Codes defined only in IMMT.

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
1	1	ir	Format/temperature indicator	3 – temperatures in tenths of °C 4 – temperatures in halves of °C 5 – temperatures in whole °C <b>[Note: codes 1-2 were previously used to refer to the obsolete IMMPC format; current codes all refer to the IMMT format]</b>
2	2-5	AAAA	Year UTC	Four digits
3	6-7	MM	Month UTC	01 – 12 January to December
4	8-9	YY	Day UTC	01 – 31
5	10-11	GG	Time of observation	Nearest whole hour UTC, WMO specifications
6	12	Qc	Quadrant of the globe	WMO code table 3333
7	13-15	L <sub>a</sub> L <sub>a</sub> L <sub>a</sub>	Latitude	Tenths of degrees, WMO specifications
8	16-19	L <sub>o</sub> L <sub>o</sub> L <sub>o</sub> L <sub>o</sub>	Longitude	Tenths of degrees
9	20		Cloud height (h) and visibility (VV) measuring indicator	0 – h and VV estimated 1 – h measured, VV estimated 2 – h and VV measured 3 – h estimated, VV measured
10	21	h	Height of clouds	WMO code table 1600
11	22-23	VV	Visibility	WMO code table 4377
12	24	N	Cloud amount	Oktas, WMO code table 2700; show 9 where applicable
13	25-26	<b>dd</b>	True wind direction	Tens of degrees, WMO code table 0877; show 00 or 99 where applicable
14	27	<b>i<sub>w</sub></b>	Indicator for wind speed	WMO code table 1855
15	28-29	ff	Wind speed	Tens and units of knots or meters per second, hundreds omitted; values in excess of 99 knots are to be indicated in units of meters per second and <b>i<sub>w</sub></b> encoded accordingly; the method of

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
				estimation or measurement and the units used (knots or meters per second) are indicated in element 14
16	30	s <sub>n</sub>	Sign of temperature	WMO code table 3845
17	31-33	TTT	Air temperature	Tenths of degrees Celsius
18	34	s <sub>t</sub>	Sign of dew-point temperature	0 – positive or zero measured dew-point temperature 1 – negative measured dew-point temperature 2 – iced measured dew-point temperature 5 – positive or zero computed dew-point temperature 6 – negative computed dew-point temperature 7 – iced computed dew-point temperature
19	35-37	T <sub>d</sub> T <sub>d</sub> T <sub>d</sub>	Dew-point temperature	Tenths of degrees Celsius
20	38-41	PPPP	Air pressure	Tenths of hectopascals
21	42-43	ww	Present weather	WMO code table 4677 or 4680
22	44	W <sub>1</sub>	Past weather	WMO code table 4561 or 4531
23	45	W <sub>2</sub>	Past weather	WMO code table 4561 or 4531
24	46	N <sub>n</sub>	Amount of lowest clouds	As reported for C <sub>L</sub> or, if no C <sub>L</sub> cloud is present, for C <sub>M</sub> , in oktas; WMO code table 2700
25	47	C <sub>L</sub>	Genus of CL clouds	WMO code table 0513
26	48	C <sub>M</sub>	Genus of CM clouds	WMO code table 0515
27	49	C <sub>H</sub>	Genus of CH clouds	WMO code table 0509
28	50	s <sub>n</sub>	Sign of sea-surface temperature	WMO code table 3845
29	51-53	T <sub>w</sub> T <sub>w</sub> T <sub>w</sub>	Sea surface temperature	Tenth of degrees Celsius
30	54		Indicator for sea-surface temperature measurement	0 – Bucket thermometer 1 – Condenser inlet 2 – Trailing thermistor 3 – Hull contact sensor 4 – "Through hull" sensor 5 – Radiation thermometer 6 – Bait tanks thermometer 7 – Others
31	55		Indicator for wave measurement	Shipborne wave recorder 0 – Wind sea and swell estimated 1 – Wind sea and swell measured 2 – Mixed wave measured, swell estimated 3 – Other combinations measured and estimated

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>				
				<table border="1"> <tr> <td>Buoy</td> <td>4 – Wind sea and swell measured 5 – Mixed wave measured, swell estimated 6 – Other combinations measured and estimated</td> </tr> <tr> <td>Other measurement system</td> <td>7 – Wind sea and swell measured 8 – Mixed wave measured, swell estimated 9 – Other combinations measured and estimated</td> </tr> </table>	Buoy	4 – Wind sea and swell measured 5 – Mixed wave measured, swell estimated 6 – Other combinations measured and estimated	Other measurement system	7 – Wind sea and swell measured 8 – Mixed wave measured, swell estimated 9 – Other combinations measured and estimated
Buoy	4 – Wind sea and swell measured 5 – Mixed wave measured, swell estimated 6 – Other combinations measured and estimated							
Other measurement system	7 – Wind sea and swell measured 8 – Mixed wave measured, swell estimated 9 – Other combinations measured and estimated							
32	56-57	P <sub>W</sub> P <sub>W</sub>	Period of wind waves or of measured waves	Whole seconds; show 99 where applicable in accordance with Note (3) under specification of P <sub>W</sub> P <sub>W</sub> in the <i>Manual on Codes</i> (WMO No. 306).				
33	58-59	H <sub>W</sub> H <sub>W</sub>	Height of wind waves or of measured waves	Half-meter values. Examples: Calm or less than ¼m to be encoded 00; 3½m to be encoded 07; 7m to be encoded 14; 11½m to be encoded 23				
34	60-61	d <sub>W1</sub> d <sub>W1</sub>	Direction of predominant swell waves	Tens of degrees, WMO code table 0877; encoded 00 or 99 where applicable. Blanks = no observation of waves attempted.				
35	62-63	P <sub>W1</sub> P <sub>W1</sub>	Period of predominant swell waves	Whole seconds; encoded 99 where applicable (see under element 32)				
36	64-65	H <sub>W1</sub> H <sub>W1</sub>	Height of predominant swell waves	Half-meter values (see under element 33)				
37	66	I <sub>s</sub>	Ice accretion on ships	WMO code table 1751				
38	67-68	E <sub>s</sub> E <sub>s</sub>	Thickness of ice accretion	In centimeters				
39	69	R <sub>s</sub>	Rate of ice accretion	WMO code table 3551				
40	70		Source of observation	0 – Unknown 1 – Logbook (paper) 2 – National Telecommunication channels 3 – National Publications 4 – Logbook (electronic) 5 – Global Telecommunication channels (GTS) 6 – International Publications [Note: Formerly (usage now discontinued); codes 1-3 also referred to "National data exchange," and codes 4-6 also referred to "International data exchange"; distinction added between paper and electronic logbook]				
41	71		Observation platform	0 – Unknown 1 – Selected ship 2 – Supplementary ship 3 – Auxiliary ship 4 – Registered VOSCLIM ship 5 – Fixed sea station (e.g., rig or platform) 6 – Coastal station [Note: 7 – Reserved] [Note: 8 – Reserved]				

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>	
				9 – Others/data buoy [Note: Formerly (usage now discontinued): code 4 referred to "Automated station/data buoy;" and codes 7-8 referred to "Aircraft" and "Satellite," respectively]	
42	72-78		Ship's call sign	Ship's call sign stored left-justified (with right-blank fill) as follows: 7-character call sign: columns 72–78 6-character call sign: columns 72–77 5-character call sign: columns 72–76 4-character call sign: columns 72–75 3-character call sign: columns 72–74	
43	79-80		Country which has recruited the ship	According to the 2-character alphabetical codes assigned by the International Organization for Standardization (ISO)	
44	81		National use		
45	82		Quality control indicator	0 – No quality control (QC) 1 – Manual QC only 2 – Automated QC only /MQC (no time-sequence checks) 3 – Automated QC only (inc. time sequence checks) 4 – Manual and automated QC (superficial; no automated time-sequence checks) 5 – Manual and automated QC (superficial; including time-sequence checks) 6 – Manual and automated QC (intensive, including automated time-sequence checks) [Note: 7 & 8 – Reserved] 9 – National system of QC (information to be furnished to WMO)	
46	83	i <sub>x</sub>	Weather data indicator	1 – Manual	
				4 – Automatic	If present and past weather data included Code tables 4677 and 4561 used
				7 – Automatic	If present and past weather data included Code tables 4680 and 4531 used
47	84	i <sub>R</sub>	Indicator for inclusion or omission of precipitation data	WMO code table 1819	
48	85-87	RRR	Amount of precipitation which has fallen during the period preceding the time of observation, as indicated by t <sub>R</sub>	WMO code table 3590	
49	88	t <sub>R</sub>	Duration of period of reference for amount of precipitation, ending	WMO code table 4019	

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
			at the time of the report	
50	89	s <sub>w</sub>	Sign of wet-bulb temperature	0 – positive or zero measured wet-bulb temperature 1 – negative measured wet-bulb temperature 2 – iced measured wet-bulb temperature 5 – positive or zero computed wet-bulb temperature 6 – negative computed wet-bulb temperature 7 – iced computed wet-bulb temperature
51	90-92	T <sub>b</sub> T <sub>b</sub> T <sub>b</sub>	Wet-bulb temperature	In tenths of degree Celsius, sign given by element 50
52	93	a	Characteristic of pressure tendency during the three hours preceding the time of observation	WMO code table 0200
53	94-96	ppp	Amount of pressure tendency at station level during the three hours preceding the time of observation	In tenths of hectopascal
54	97	D <sub>s</sub>	True direction of resultant displacement of the ship during the three hours preceding the time of observation	WMO code table 0700
55	98	v <sub>s</sub>	Ship's average speed made good during the three hours preceding the time of observation	WMO code table 4451
56	99-100	d <sub>w2</sub> d <sub>w2</sub>	Direction of secondary swell waves	Tens of degrees, WMO code table 0877; encoded 00 or 99 where applicable. Blanks – no observation of waves attempted.
57	101-102	P <sub>w2</sub> P <sub>w2</sub>	Period of secondary swell waves	Whole seconds; encoded 99 where applicable (see under element 32)
58	103-104	H <sub>w2</sub> H <sub>w2</sub>	Height of secondary swell waves	Half-meter values (see under element 33)
59	105	c <sub>i</sub>	Concentration or arrangement of sea ice	WMO code table 0639
60	106	S <sub>i</sub>	Stage of development	WMO code table 3739
61	107	b <sub>i</sub>	Ice of land origin	WMO code table 0439
62	108	D <sub>i</sub>	True bearing of principal ice edge	WMO code table 0739

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
63	109	Z <sub>i</sub>	Present ice situation and trend of conditions over the preceding three hours	WMO code table 5239
64	110		FM code version	0 – previous to FM 24-V 1 – FM 24-V 2 – FM 24-VI Ext. 3 – FM 13-VII 4 – FM 13-VIII 5 – FM 13-VIII Ext. 6 – FM 13-IX 7 – FM 13-IX Ext. 8 – FM 13-X 9 – FM 13-XI A – FM 13-XII Ext. [Note: etc. for future configurations]
65	111		IMMT version	0 – IMMT version just prior to version number being included 1 – IMMT-I (in effect from Nov. 1994) 2 – IMMT-II (in effect from Jan. 2003) 3 – IMMT-III (in effect from Jan. 2006) 4 – IMMT-IV (this version) [Note: etc. for future configurations]
66	112	Q <sub>1</sub>	Quality control indicator for (h)	0 – no quality control (QC) has been performed on this element 1 – QC has been performed; element appears to be correct 2 – QC has been performed; element appears to be inconsistent with other elements 3 – QC has been performed; element appears to be doubtful 4 – QC has been performed; element appears to be erroneous 5 – The value has been changed as a result of QC 6 – The flag as received by the GCCs was set to “1” (correct), but the element was judged by their MQCS as either inconsistent, dubious, erroneous or missing 7 – The flag as received by the GCCs was set to “5” (amended) but the element was judged by their MQCS as inconsistent, dubious, erroneous or missing [Note: 8 – Reserved] 9 – The value of the element is missing
67	113	Q <sub>2</sub>	QC indicator for (VV)	- idem -
68	114	Q <sub>3</sub>	QC indicator for (clouds: elements 12, 24–27)	- idem -
69	115	Q <sub>4</sub>	QC indicator for (dd)	- idem -
70	116	Q <sub>5</sub>	QC indicator for (ff)	- idem -
71	117	Q <sub>6</sub>	QC indicator for (TTT)	- idem -
72	118	Q <sub>7</sub>	QC indicator for (T <sub>d</sub> T <sub>d</sub> T <sub>d</sub> )	- idem -

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
73	119	Q <sub>8</sub>	QC indicator for (PPPP)	- idem -
74	120	Q <sub>9</sub>	QC indicator for (weather: elements 21–23)	- idem -
75	121	Q <sub>10</sub>	QC indicator for (T <sub>w</sub> T <sub>w</sub> T <sub>w</sub> )	- idem -
76	122	Q <sub>11</sub>	QC indicator for (P <sub>w</sub> P <sub>w</sub> )	- idem -
77	123	Q <sub>12</sub>	QC indicator for (H <sub>w</sub> H <sub>w</sub> )	- idem -
78	124	Q <sub>13</sub>	QC indicator for (swell: elements 34–36, 56–58)	- idem -
79	125	Q <sub>14</sub>	QC indicator for (i <sub>R</sub> RRR <sub>R</sub> )	- idem -
80	126	Q <sub>15</sub>	QC indicator for (a)	- idem -
81	127	Q <sub>16</sub>	QC indicator for (ppp)	- idem -
82	128	Q <sub>17</sub>	QC indicator for (D <sub>s</sub> )	- idem -
83	129	Q <sub>18</sub>	QC indicator for (v <sub>s</sub> )	- idem -
84	130	Q <sub>19</sub>	QC indicator for (T <sub>b</sub> T <sub>b</sub> T <sub>b</sub> )	- idem -
85	131	Q <sub>20</sub>	QC indicator for ships' position	- idem -
86	132	Q <sub>21</sub>	Version identification for Minimum quality control standards (MQCS)	1 – MQCS- I (Original version, Feb. 1989): CMM-X 2 – MQCS-II (Version 2, March 1997) CMM-XII 3 – MQCS-III (Version 3, April 2000) SGM-C-VIII 4 – MQCS-IV (Version 4, June 2001): JCOMM-I 5 – MQCS-V (Version 5, July 2004): ETMC-I 6 – MQCS-VI (this version, to be agreed) [Note: etc. for future configurations]
87	133-135	HDG	Additional Requirements for VOSClm: Ship's heading; the direction to which the bow is pointing, referenced to true North	(000-360); e.g. 360 = North 000 = No Movement 090 = East
88	136-138	COG	Ship's ground course; the direction the vessel actually moves over the fixed earth and referenced to True North	(000-360); e.g. 360 = North 000 = No Movement 090 = East

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
89	139-140	SOG	Ship's ground speed; the speed the vessel actually moves over the fixed earth	(00-99); Round to nearest whole knot
90	141-142	SLL	Maximum height in meters of deck cargo above Summer maximum load line	(00-99); report to nearest whole meter
91	143	s <sub>L</sub>	Sign of departure of reference level	0 = positive or zero, 1 = negative
92	144-145	hh	Departure of reference level (Summer maximum load line) from actual sea level	(00-99) is the difference to the nearest whole meter between the Summer maximum load line and the sea level. Consider the difference positive when the Summer maximum load line is above the level of the sea and negative if below the water line.
93	146-148	RWD	Relative wind direction in degrees off the bow	Relative wind direction; e.g. 000 = no apparent relative wind speed (calm conditions on deck). Reported direction for relative wind = 001-360 degrees in a clockwise direction off the bow of the ship. When directly on the bow, RWD = 360.
94	149-151	RWS	Relative wind speed indicated by $i_w$ (knots or $m s^{-1}$ )	Reported in either whole knots or whole meters per second (e.g. 010 knots or 005 $m s^{-1}$ ). Units established by $i_w$ (element 14) [Note: RWS is a 3-character field to store values of RWS larger than ff (if $i_w$ indicates knots), e.g. ff=98 knots, RWS=101 knots; see also element 15.]
95	152	Q <sub>22</sub>	QC indicator for (HDG)	[Note: coding as for element 66]
96	153	Q <sub>23</sub>	QC indicator for (COG)	– idem –
97	154	Q <sub>24</sub>	QC indicator for (SOG)	– idem –
98	155	Q <sub>25</sub>	QC indicator for (SLL)	– idem –
	156	blank		[Note: Formerly (usage now discontinued): QC indicator for (s <sub>L</sub> ); now Q <sub>27</sub> serves as the indicator for both s <sub>L</sub> and hh]
99	157	Q <sub>27</sub>	QC indicator for (S <sub>L</sub> and hh)	– idem –
100	158	Q <sub>28</sub>	QC indicator for (RWD)	– idem –
101	159	Q <sub>29</sub>	QC indicator for (RWS)	– idem –

<u>Element Number</u>	<u>Character Number</u>	<u>Code</u>	<u>Element</u>	<u>Coding procedure</u>
			Fields new for IMMT-IV:	
102	160-163	RH	Relative humidity	Tenths of Percentage
103	164	RHi	Relative humidity indicator	0 – Relative humidity in tenths of Percentage, measured and originally reported 1 – Relative humidity in whole Percentage, measured and originally reported [Note: 2 – Reserved] 3 – Relative humidity in tenths of Percentage, computed 4 – Relative humidity in whole Percentage, computed
104	165	AWSi	AWS indicator	1 – Automated Weather Station (AWS) 2 – Automated Weather Station plus Manual Observation
105	166-172	IMOno	IMO number	Seven digits (or left justified with right-blank fill)

---

Annex 2 to draft Recommendation 12/1 (JCOMM-III)

AMENDMENTS TO THE *MANUAL ON MARINE METEOROLOGICAL SERVICES* (WMO-No. 558) AND *GUIDE TO MARINE METEOROLOGICAL SERVICES* (WMO-No. 471)

MINIMUM QUALITY CONTROL STANDARD (MQCS)  
MQCS-VI (Version 6)

Notes:

- (a) **Highlighting** marks changes with respect to MQCS-V
- (b) See the specifications for setting quality control Indicators  $Q_1$  to  $Q_{29}$  at the end of this Annex
- (c)  $\Delta$  = space (ASCII 32)

<u>Element</u>	<u>Error</u>	<u>Action</u>
1	$i_T \neq 3 - 5, \Delta$	Correct manually otherwise <b>3</b>
2	AAAA $\neq$ valid year	Correct manually otherwise reject
3	MM $\neq$ 01 - 12	Correct manually otherwise reject
4	YY $\neq$ valid day of month	Correct manually otherwise reject
5	GG $\neq$ 00 - 23	Correct manually otherwise reject
6	$Q_c \neq 1, 3, 5, 7$ $Q_c = \Delta$	Correct manually and $Q_{20} = 5$ , otherwise $Q_{20} = 4$ $Q_{20} = 2$
7	$L_a L_a L_a \neq 000-900$ $L_a L_a L_a = \Delta\Delta\Delta$	Correct manually and $Q_{20} = 5$ , otherwise $Q_{20} = 4$ $Q_{20} = 2$
8	$L_o L_o L_o L_o \neq 0000-1800$ $L_o L_o L_o L_o = \Delta\Delta\Delta\Delta$ $L_a L_a L_a = L_o L_o L_o L_o = \Delta\Delta\Delta(\Delta)$	Correct manually and $Q_{20} = 5$ , otherwise $Q_{20} = 4$ $Q_{20} = 2$ Correct manually otherwise reject
<u>Time sequence checks</u>		
	Change in latitude $> 0.7^\circ/\text{hr}$	Correct manually otherwise $Q_{20} = 3$
	Change in longitude $> 0.7^\circ/\text{hr}$ when lat. 00-39.9	Correct manually otherwise $Q_{20} = 3$
	Change in longitude $> 1.0^\circ/\text{hr}$ when lat. 40-49.9	Correct manually otherwise $Q_{20} = 3$
	Change in longitude $> 1.4^\circ/\text{hr}$ when lat. 50-59.9	Correct manually otherwise $Q_{20} = 3$
	Change in longitude $> 2.0^\circ/\text{hr}$ when lat. 60-69.9	Correct manually otherwise $Q_{20} = 3$
	Change in longitude $> 2.7^\circ/\text{hr}$ when lat. 70-79.9	Correct manually otherwise $Q_{20} = 3$
<b>9</b>	<b>Indicator <math>\neq</math> 0-3, <math>\Delta</math></b>	<b>Correct manually, otherwise <math>\Delta</math></b>
10	$h \neq 0-9$ $h = \Delta$	Correct manually and $Q_1 = 5$ , otherwise $Q_1 = 4$ $Q_1 = 9$
11	$VV \neq 90-99$ $VV = \Delta\Delta$	Correct manually and $Q_2 = 5$ , otherwise $Q_2 = 4$ $Q_2 = 9$
12	$N \neq 0-9, \Delta$ $N < N_n$	Correct manually and $Q_3 = 5$ , otherwise $Q_3 = 4$ Correct manually and $Q_3 = 5$ , otherwise $Q_3 = 2$
13	$dd \neq 00-36, 99$ $dd = \Delta\Delta$ dd versus ff $dd = 00, ff \neq 00$  $dd \neq 00, ff = 00$	Correct manually and $Q_4 = 5$ , otherwise $Q_4 = 4$ $Q_4 = 9$  Correct manually and $Q_4$ or $Q_5 = 5$ otherwise $Q_4 = Q_5 = 2$ Correct manually and $Q_4$ or $Q_5 = 5$ otherwise $Q_4 = Q_5 = 2$
14	$i_w \neq 0, 1, 3, 4$	Correct manually, otherwise $Q_5 = Q_{29} = 4$
15	$ff > 80$ knots $ff = \Delta\Delta$	Correct manually and $Q_5 = 5$ , otherwise $Q_5 = 3$ $Q_5 = 9$
16	$s_n \neq 0, 1$	Correct manually, otherwise $Q_6 = 4$
17	TTT = $\Delta\Delta\Delta$ If $-25 > \text{TTT} > 40$ then when Lat. $< 45.0$ TTT $< -25$	$Q_6 = 9$          $Q_6 = 4$

<u>Element</u>	<u>Error</u>	<u>Action</u>
	TTT > 40 when Lat. ≥ 45.0	Q <sub>6</sub> = 3
	TTT < -25	Q <sub>6</sub> = 3
	TTT > 40	Q <sub>6</sub> = 4
<u>TTT versus humidity parameters</u>		
	TTT < WB (wet bulb)	Correct manually and Q <sub>6</sub> = 5, otherwise Q <sub>6</sub> =Q <sub>19</sub> = 2
	TTT < DP (dew point)	Correct manually and Q <sub>6</sub> = Q <sub>7</sub> = 5, otherwise Q <sub>6</sub> = Q <sub>7</sub> = 2
18	s <sub>t</sub> ≠ 0, 1, 2, 5, 6, 7	Correct manually, otherwise Q <sub>7</sub> = 4
19	DP > WB DP > TTT	Correct manually and Q <sub>7</sub> = 5, otherwise Q <sub>7</sub> =Q <sub>19</sub> = 2
20	WB = DP = ΔΔΔ 930 > PPPP > 1050 hPa 870 > PPPP > 1070 hPa PPPP = ΔΔΔΔ	Correct manually and Q <sub>8</sub> = 5, otherwise Q <sub>8</sub> = 3 Correct manually and Q <sub>8</sub> = 5, otherwise Q <sub>8</sub> = 4 Q <sub>8</sub> = 9
21	ww = 22-24, 26, 36-39, 48, 49, 56, 57, 66-79, 83-88 93-94 and latitude <20° if i <sub>x</sub> = 7: w <sub>a</sub> w <sub>a</sub> = 24 - 25, 35, 47-48, 54-56, 64-68, 70-78, 85-87 and latitude <20°	Correct manually and Q <sub>9</sub> = 5, otherwise Q <sub>9</sub> = 4 Correct manually and Q <sub>9</sub> = 5, otherwise Q <sub>9</sub> = 3
22, 23	W <sub>1</sub> or W <sub>2</sub> = 7 and latitude <20° W <sub>1</sub> < W <sub>2</sub> W <sub>1</sub> = W <sub>2</sub> = ww = ΔΔΔΔ	Correct manually and Q <sub>9</sub> = 5, otherwise Q <sub>9</sub> = 4 Correct manually and Q <sub>9</sub> = 5, otherwise Q <sub>9</sub> = 2 Q <sub>9</sub> = 9
24-27	N = 0, and N <sub>h</sub> C <sub>L</sub> C <sub>M</sub> C <sub>H</sub> ≠ 0000 N = Δ, and N <sub>h</sub> C <sub>L</sub> C <sub>M</sub> C <sub>H</sub> ≠ ΔΔΔΔ N = 9, and not (N <sub>h</sub> = 9 and C <sub>L</sub> C <sub>M</sub> C <sub>H</sub> ≠ ΔΔΔ N=Δ, and N <sub>h</sub> C <sub>L</sub> C <sub>M</sub> C <sub>H</sub> =ΔΔΔΔ	Correct manually and Q <sub>3</sub> = 5, otherwise Q <sub>3</sub> = 2 Correct manually and Q <sub>3</sub> = 5, otherwise Q <sub>3</sub> = 2 Correct manually and Q <sub>3</sub> = 5, otherwise Q <sub>3</sub> = 2 Q <sub>3</sub> = 9
28	s <sub>n</sub> ≠ 0, 1	Correct manually otherwise Q <sub>10</sub> = 4
29	T <sub>w</sub> T <sub>w</sub> T <sub>w</sub> = ΔΔΔ if -2.0 > T <sub>w</sub> T <sub>w</sub> T <sub>w</sub> > 37.0 then when Lat. < 45.0 T <sub>w</sub> T <sub>w</sub> T <sub>w</sub> < -2.0 T <sub>w</sub> T <sub>w</sub> T <sub>w</sub> > 37.0 when Lat. ≥ 45.0 T <sub>w</sub> T <sub>w</sub> T <sub>w</sub> < -2.0 T <sub>w</sub> T <sub>w</sub> T <sub>w</sub> > 37.0	Q <sub>10</sub> = 9 Control manually and Q <sub>10</sub> = 5, otherwise Q <sub>10</sub> = 4 Control manually and Q <sub>10</sub> = 5, otherwise Q <sub>10</sub> = 3 Control manually and Q <sub>10</sub> = 5, otherwise Q <sub>10</sub> = 3 Control manually and Q <sub>10</sub> = 5, otherwise Q <sub>10</sub> = 4
30	Indicator ≠ 0-7, Δ	Correct manually, otherwise Δ
31	Indicator ≠ 0-9, Δ	Correct manually, otherwise Δ
32	20 < P <sub>w</sub> P <sub>w</sub> < 30 P <sub>w</sub> P <sub>w</sub> ≥ 30 and ≠ 99 P <sub>w</sub> P <sub>w</sub> = ΔΔ	Q <sub>11</sub> = 3 Q <sub>11</sub> = 4 Q <sub>11</sub> = 9
33	35 < H <sub>w</sub> H <sub>w</sub> < 50 H <sub>w</sub> H <sub>w</sub> ≥ 50 H <sub>w</sub> H <sub>w</sub> = ΔΔ	Q <sub>12</sub> = 3 Q <sub>12</sub> = 4 Q <sub>12</sub> = 9
34	d <sub>w1</sub> d <sub>w1</sub> ≠ 00-36, 99 swell <sub>1</sub> = swell <sub>2</sub> = Δ	Correct manually and Q <sub>13</sub> = 5, otherwise Q <sub>13</sub> = 4 Q <sub>13</sub> = 9
35	25 < P <sub>w1</sub> P <sub>w1</sub> < 30 P <sub>w1</sub> P <sub>w1</sub> ≥ 30 and ≠ 99	Q <sub>13</sub> = 3 Q <sub>13</sub> = 4
36	35 < H <sub>w1</sub> H <sub>w1</sub> < 50 H <sub>w1</sub> H <sub>w1</sub> ≥ 50	Q <sub>13</sub> = 3 Q <sub>13</sub> = 4
37	I <sub>s</sub> ≠ 1-5, Δ	Correct manually, otherwise Δ
38	E <sub>s</sub> E <sub>s</sub> ≠ 00-99, ΔΔ	Correct manually, otherwise ΔΔ
39	R <sub>s</sub> ≠ 0-4, Δ	Correct manually, otherwise Δ
40	Source ≠ 0-6	Correct manually, otherwise Δ
41	Platform ≠ 0-9	Correct manually, otherwise Δ
42	No call sign	Insert manually, mandatory entry

<u>Element</u>	<u>Error</u>	<u>Action</u>
43	No country code	Insert manually
44	No Quality Control	
45	Q ≠ 0-6, 9	Correct manually, otherwise Δ
46	i <sub>x</sub> ≠ 1-7	Correct manually, otherwise Δ
47	i <sub>R</sub> = 0-2 and RRR = 000, ΔΔΔ	Correct manually, otherwise Q <sub>14</sub> = 4
	i <sub>R</sub> = 3 and RRR ≠ ΔΔΔ	Correct manually, otherwise Q <sub>14</sub> = 2
	i <sub>R</sub> = 4 and RRR ≠ ΔΔΔ	Correct manually, otherwise Q <sub>14</sub> = 2
	i <sub>R</sub> ≠ 0-4	Correct manually, otherwise Q <sub>14</sub> = 4
48	RRR ≠ 001-999 and iR = 1, 2	Correct manually and Q <sub>14</sub> = 5, otherwise Q <sub>14</sub> = 2
49	t <sub>R</sub> ≠ 0-9, Δ	Correct manually and Q <sub>14</sub> = 5, otherwise Q <sub>14</sub> = 4
50	s <sub>w</sub> ≠ 0, 1, 2, 5, 6, 7	Correct manually, otherwise Q <sub>19</sub> = 4
51	WB < DP	Correct manually and Q <sub>19</sub> = 5, otherwise Q <sub>19</sub> =Q <sub>7</sub> =2
	WB = ΔΔΔ	Q <sub>19</sub> = 9
52	WB > TTT	Correct manually and Q <sub>19</sub> = 5, otherwise Q <sub>19</sub> =Q <sub>6</sub> =2
	a ≠ 0-8	Correct manually and Q <sub>15</sub> = 5, otherwise Q <sub>15</sub> = 4
	a = 4 and ppp ≠ 000	Correct manually and Q <sub>15</sub> or Q <sub>16</sub> = 5, otherwise Q <sub>15</sub> =Q <sub>16</sub> =2
	a = 1,2,3,6,7,8 and ppp=000	Correct manually and Q <sub>15</sub> or Q <sub>16</sub> = 5, otherwise Q <sub>15</sub> =Q <sub>16</sub> = 2
53	a = Δ	Q <sub>15</sub> = 9
	250 ≥ ppp > 150	Correct manually and Q <sub>16</sub> = 5, otherwise Q <sub>16</sub> = 3
	ppp > 250	Correct manually and Q <sub>16</sub> = 5 otherwise Q <sub>16</sub> = 4
54	ppp = ΔΔΔ	Q <sub>16</sub> = 9
	D <sub>s</sub> ≠ 0-9	Correct manually and Q <sub>17</sub> = 5, otherwise Q <sub>17</sub> = 4
55	D <sub>s</sub> = Δ	Q <sub>17</sub> = 9
	V <sub>s</sub> ≠ 0-9	Correct manually and Q <sub>18</sub> = 5, otherwise Q <sub>18</sub> = 4
56	V <sub>s</sub> = Δ	Q <sub>18</sub> = 9
	d <sub>w2</sub> d <sub>w2</sub> ≠ 00-36, 99, ΔΔ	Correct manually and Q <sub>13</sub> = 5, otherwise Q <sub>13</sub> = 4
57	25 < P <sub>w2</sub> P <sub>w2</sub> < 30	Q <sub>13</sub> = 3
	P <sub>w2</sub> P <sub>w2</sub> ≥ 30 and ≠99	Q <sub>13</sub> = 4
58	35 < H <sub>w2</sub> H <sub>w2</sub> < 50	Q <sub>13</sub> = 3
	H <sub>w2</sub> H <sub>w2</sub> ≥ 50	Q <sub>13</sub> = 4
59	c <sub>i</sub> ≠ 0-9, Δ	Correct manually, otherwise Δ
60	S <sub>i</sub> ≠ 0-9, Δ	Correct manually, otherwise Δ
61	b <sub>i</sub> ≠ 0-9, Δ	Correct manually, otherwise Δ
62	D <sub>i</sub> ≠ 0-9, Δ	Correct manually, otherwise Δ
63	z <sub>i</sub> ≠ 0-9, Δ	Correct manually, otherwise Δ
64	version ≠ 0-9, A, Δ	Correct manually, otherwise Δ
65	version ≠ 0-4, Δ	Correct manually, otherwise Δ
86	Minimum Quality Control Standard (MQCS) version identification	1= MQCS-I (Original version, Feb. 1989) CMM-X 2= MQCS-II (Version 2, March 1997) CMM-XII 3= MQCS-III (Version 3, April 2000) SGMC-VIII 4= MQCS-IV (Version 4, June 2001) JCOMM-I 5= MQCS-V (Version 5, July 2004) ETMC-I 6 = MQCS-VI (this version, to be agreed)
87	HDG ≠ 000-360	Correct manually and Q <sub>22</sub> = 5, otherwise Q <sub>22</sub> = 4
88	HDG = ΔΔΔ	Q <sub>22</sub> = 9
	COG ≠ 000-360	Correct manually and Q <sub>23</sub> = 5, otherwise Q <sub>23</sub> = 4
89	COG = ΔΔΔ	Q <sub>23</sub> = 9
	SOG ≠ 00 - 99	Correct manually and Q <sub>24</sub> = 5, otherwise Q <sub>24</sub> = 4
90	SOG = ΔΔ	Q <sub>24</sub> = 9
	SOG > 33	Correct manually and Q <sub>24</sub> = 5, otherwise Q <sub>24</sub> = 3
	SLL ≠ 00-99	Correct manually and Q <sub>25</sub> = 5, otherwise Q <sub>25</sub> = 4
91	SLL = ΔΔ	Q <sub>25</sub> = 9
	SLL > 40	Correct manually and Q <sub>25</sub> = 5, otherwise Q <sub>25</sub> = 3
92	s <sub>L</sub> ≠ 0,1	Correct manually and Q <sub>27</sub> = 5, otherwise Q <sub>27</sub> = 4
92	hh ≠ 00 – 99	Correct manually and Q <sub>27</sub> = 5, otherwise Q <sub>27</sub> = 4
	hh = ΔΔ	Q <sub>27</sub> = 9
	hh >= 13	Correct manually and Q <sub>27</sub> = 5, otherwise Q <sub>27</sub> = 3

<u>Element</u>	<u>Error</u>	<u>Action</u>
<b>93</b>	hh < -01 RWD ≠ 000 - 360, 999 RWD = ΔΔΔ	Correct manually and Q <sub>27</sub> = 5, otherwise Q <sub>27</sub> = 4 Correct manually and Q <sub>28</sub> = 5, otherwise Q <sub>28</sub> = 4 Q <sub>28</sub> = 9
<b>94</b>	RWS ≠ 000 - 999 RWS = ΔΔΔ RWS > 110 kts	Correct manually and Q <sub>29</sub> = 5, otherwise Q <sub>29</sub> = 4 Q <sub>28</sub> = 9 Correct manually and Q <sub>29</sub> = 5, otherwise Q <sub>29</sub> = 3
<u>RWD versus RWS</u>		
	RWD = 000, RWS ≠ 000	Correct manually and Q <sub>28</sub> or Q <sub>29</sub> = 5, otherwise Q <sub>28</sub> = Q <sub>29</sub> = 2
	RWD ≠ 000, RWS = 000	Correct manually and Q <sub>28</sub> or Q <sub>29</sub> = 5, otherwise Q <sub>28</sub> = Q <sub>29</sub> = 2
<u>Specifications for setting quality control Indicators Q<sub>1</sub> to Q<sub>29</sub></u>		
0	No quality control (QC) has been performed on this element	
1	QC has been performed; element appears to be correct	
2	QC has been performed; element appears to be inconsistent with other elements	
3	QC has been performed; element appears to be doubtful	
4	QC has been performed; element appears to be erroneous	
5	The value has been changed as a result of QC	
<b>6</b>	The original flag is set "1" (correct) and the value will be classified by MQCS as inconsistent, dubious, erroneous or missing	
<b>7</b>	The original flag is set "5" (amended) and the value will be classified by MQCS as inconsistent, dubious, erroneous or missing	
8	Reserve	
9	The value of the element is missing	